

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

A

10/14/99  
JC678 U.S. PTO  
09/417604

In re Patent Application of )  
)  
Akira Ishino, Katsuaki Kouno and Colin )  
Buckley )  
)  
For: PACKAGING SYSTEM )  
INCORPORATING A PRINTER )  
)

Attorney Docket No.  
8005.166US0

San Francisco, California

JC678 U.S. PTO  
09/417604  
10/14/99

**Box Patent Application**  
Assistant Commissioner for Patents  
Washington, D.C. 20231

By Express Mail No: EL03335559US  
Dated: October 14, 1999

PATENT APPLICATION TRANSMITTAL

Sir:


Transmitted herewith for filing is the patent application of inventors AKIRA  
ISHINO, KATSUAKI KOUNO and COLIN BUCKLEY for "PACKAGING SYSTEM  
INCORPORATING A PRINTER." Enclosed are:

1. Fifteen (15) pages of the specification, including sixteen (16) claims and an abstract.
2. Six (6) sheets of drawings.
3. A DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION of the inventors.
4. An ASSIGNMENT of the invention to ISHIDA CO., LTD., Form PTO-1595, and a check to cover the \$40.00 fee.
5. Certified copy of Japanese Appln. 10-314042, filed October 15, 1998, upon which this application claims priority.
6. Please send all correspondence related to this application to Keiichi Nishimura, Reg. No. 29,093 at:

Majestic, Parsons, Siebert & Hsue P.C.  
Four Embarcadero Center, Suite 1100  
San Francisco, California 94111-4106  
Telephone: (415) 248-5500  
Facsimile: (415) 362-5418

The filing fee is calculated to be \$760.00, a check for which is enclosed. The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment, to Deposit Account No. 13-1030. This authorization is provided in duplicate.

Dated: October 14, 1999.



---

Keiichi Nishimura (Reg. No. 29,093)  
MAJESTIC, PARSONS, SIEBERT & HSUE P.C.  
Four Embarcadero Center, Suite 1100  
San Francisco, California 94111-4106  
Telephone: (415) 248-5500  
Facsimile: (415) 362-5418

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE  
APPLICATION FOR PATENT

**PACKAGING SYSTEM INCORPORATING A PRINTER**

Inventors: Akira Ishino  
Katsuaki Kouno  
Colin Buckley

5

**Background of the Invention**

10 This invention relates to a packaging system. It has been known to form a system incorporating both a packaging machine and a printer for making packages. Japanese Patent Publication Tokkai 4-128105, for example, disclosed such a system incorporating a so-called vertical pillow type form-fill-seal package maker and a printer. An elongated bag-making material, herein referred to as the film, is pulled out of a roll and after data such as the date of production of the packaged products are printed thereon by the printer, the film is  
15 bent and made into a tubular form by means of a longitudinal sealer adapted to seal the mutually overlapped side edges of the film together. After articles to be packaged are dropped into this tubularly formed film, it is transversely sealed above the articles captured inside and cut, and this production process is repeated.

20 Since films with different sizes and different designs thereon are used for producing packaged products of different kinds, however, the initial position at which the printer should start printing also changes, depending on the kind of products to be made. Thus, data related to the printing such as the printing position must be set, as well as packaging conditions such as the width  
25 and the length of the bags to be formed, for each of different kinds of products to be packaged. Such setting operations are cumbersome to perform because the conditions for the packaging and the data related to the printing are separately set by using independent controllers of the packaging machine and the printer,

respectively. Moreover, every time the kind of products to be produced is changed, not only new packaging conditions but also new data for the printing corresponding to these packaging conditions must be set. Thus, errors have been likely to occur in setting these conditions and data.

5

### Summary of the Invention

It is therefore an object of this invention to provide an improved packaging system incorporating a printer with which data for the printing can be easily set corresponding to a selected packaging condition such that errors in the setting of these data are not likely to occur.

A packaging system embodying this invention, with which the above and other objects can be accomplished, may be characterized as comprising not only a packaging machine of a known kind, which transports a bag-making film, forms it into a tubular form, fills it with articles to be packaged and seals it to produce a packaged product, and a printer, also of a known kind, disposed along the film path for making prints on the film, but also a packaging condition memory which stores packaging conditions for operating the packaging machine, a print data memory which stores print data for operating the printer, and a correlation data memory which stores the print data in correlation with the packaging conditions. These memories are parts of a control unit for the system and, when a packaging condition is selected through an input device, not only is the packaging machine operated under the specified condition but also the printer is operated by the data which correspond to the selected packaging condition according to correlation data stored in the correlation data memory.

With a system thus characteristically structured, the packaging conditions for the packaging machine and the print data for the printer can be set automatically, and hence easily, in a properly correlated manner. Since this correlation is stored in one of its memory devices, errors in matching a packaging condition and print data can be reliably avoided. Throughout herein, the expression "packaging conditions" is used to indicate conditions for operating the

packaging machine such as the length and width of the bags to be produced and the number of packaged products to be produced thereby. Expressions "print data" will be used to indicate items such as the position of printing, the font and size of the characters to be printed, and the intervals between characters and lines of characters.

#### Brief Description of the Drawings

The accompanying drawings, which are incorporated in and form a part of this specification, illustrate embodiments of the invention and, together with the description, serve to explain the principles of the invention. In the drawings:

Fig. 1 is a schematic side view of a packaging system embodying this invention including a boxing system for putting packaged products into boxes;

Fig. 2 is a block diagram of a control part of the packaging system of Fig. 1;

Figs. 3A and 3B and 3C show schematically how data are stored respectively in the packaging condition memory, the print data memory and the correlation data memory;

Fig. 4A, is a plan view of a portion of the film, Fig. 4B is a plan view of a packaged product, and Fig. 4C is a plan view of the printed portion of the film to define the meaning of line width and line interval;

Figs. 5A, 5B, 5C and 5D are examples of a display which may appear on the touch screen on various occasions; and

Fig. 6 is a block diagram of a control part of another packaging system embodying this invention, in which like or equivalent components are indicated by the same numerals as in Fig. 2.

### Detailed Description of the Invention

The invention is described next by way of an example. Fig. 1 shows a packaging system embodying this invention, including a conveyor 100, a combinational weigher 1, a form-fill-seal package making machine (herein referred to as the "packaging machine") 200, a weight checker 300 and a boxing machine 700. The conveyor 100 is for transporting articles M to be packaged to form products M1 and dropping them to the combinational weigher 1. The combinational weigher 1 is of a known kind, serving to combine the articles M supplied into a plurality of its weigh hoppers (not shown) to select a combination having a desired total weight satisfying a preliminarily determined condition with respect to a target weight and to drop the articles M of the selected combination. The packaging machine 200 is of a so-called vertical pillow type, serving to pull a film F out of a film roll Fr, to longitudinally seal its mutually overlapped side edges by means of a longitudinal sealer 201 to make it into a tubular form and, after the articles M dropped from above fills the tubularly formed film F, to transversely seal it transversely at a seal position F1 above the captured articles by means of a transverse sealer 202 (as described, for example, in Japanese Patent Publication Tokkai 4-128105).

A printer 40 and a print roller 41 are disposed by the path along which the film F is transported from the film roll Fr to the longitudinal sealer 201. The printer 40 may be of a thermal transfer type which prints one line at a time by pressing a heated printer head onto an ink ribbon as the film F passes between the printer 40 and the print roller 41.

Packaged products M1 are dropped one at a time from the packaging machine 200, pushed by a pusher 301 (the movement of which is indicated by a double-headed arrow) to fall in the forward direction (to the right in Fig. 1) onto a receiving conveyor 302, and transported to the boxing machine 700 on the downstream end, passing through the weigher conveyor 303, a seal checker 400, a sorter 500 and an aligner 600. The boxing machine 700 is for placing these packaged products M1 in cardboard boxes B.

Next, the control part of the packaging system shown in Fig. 1 will be described. As schematically shown in Fig. 2, a packaging controller 20 and a printer controller 30 are respectively connected through an interface (not shown) to the packaging machine 200 and the printer 40, and they are themselves  
 5 connected to each other through another interface (not shown). Another controller 50 for controlling other components (indicated summarily by numeral 51) such as the combinational weigher 1, the weight checker 300, the seal checker 400 and the boxing machine 700 is also connected to the packaging controller 20 through still another interface (not shown).

10 The packaging controller 20 includes a CPU, a ROM and a RAM (herein respectively referred to as the "first CPU" or "CPU No. 1" 21, the "first ROM" or "ROM No. 1" 22 and the "first RAM" or "RAM No. 1" 23. The first RAM 23 includes a memory (herein referred to as the "packaging condition memory 24" for storing packaging conditions such as the packaging condition  
 15 numbers, packaging condition names (or product names), bag length, back width, packaging speed (or the number of packaged products M1 produced per minute) and the timing of sealing, as shown in Fig. 3A, in a mutually correlated manner. There is also another memory (herein referred to as the "correlation data memory 25"), to be described below, included in the first RAM 23. The first CPU 21  
 20 serves to control the package making operations of the packaging machine 200 on the basis of packaging conditions retrieved from the packaging condition memory 24.

As shown in Fig. 4A and 4B, marks Fm are already printed on the right-hand side edge of the film F at a specified pitch P equal to the length of the  
 25 bags to be made therefrom. These marks Fm serve as reference positions not only for the transverse sealing but also for the printing. An optical detector 27, disposed between the film roll Fr and the printer 40 as shown in Fig. 1, for detecting these marks Fm is connected through an interface (not shown) to the packaging controller 20. Whenever the optical detector 27 detects one of these  
 30 marks Fm as the film F is unwound from the roll Fr during the course of a normal

packaging operation, a detection signal is outputted therefrom to the packaging controller 20. When this signal is received, the first CPU 21 responds by outputting a print command to the printer controller 30, causing the printer 40 to start its printing operations at a specified timing.

5           A touch screen 26 is also connected to the packaging controller 20, serving in well known manners not only as a display means for displaying various data and/or menus on its display screen but also as an input means for allowing the user to make an input by touching the screen with a finger at indicated positions.

10           The printer controller 30 includes a CPU, a ROM, a RAM (which are respectively referred to as the "second CPU" or "CPU No.2" 31, the "second ROM" or "ROM No. 2" 32, and the "second RAM" or "RAM No. 2" 33) and a time-counting clocking device 35, as shown in Fig. 2. The second RAM 33 includes a memory (herein referred to as the "print data memory 34") for storing  
15           print data such as print data numbers, print data names, font to be used for the printing, character size, line width  $L_w$ , line interval  $L_l$ , and printing positions  $x$  and  $y$ , as shown in Fig. 3B, in a mutually correlated manner. The printing positions  $x$  and  $y$  respectively indicate the distance in the transverse direction between the mark  $F_m$  and the left-hand edge of the printing position and the  
20           distance in the lengthwise direction between the mark  $F_m$  and the upper edge of the printing position. As shown in Fig. 4C, the line width  $L_w$  means the pitch between mutually adjacent characters in a line and the line interval  $L_l$  means the pitch between mutually adjacent lines. These print data are preliminarily stored in the print data memory 34 and may be inputted through a personal computer 8, as  
25           shown in Fig. 2, adapted to be connected through an interface (not shown) to the printer controller 30 whenever necessary.

          The clocking device 35, included in the printer controller 30, serves to output the current date to the second CPU 31. The second CPU 31 treats this received current date as the production date and calculates the last  
30           date, or expiration date, by which the packaged product should be sold, or



consumed, by adding a specified number of days to the current date. When the print command outputted from the packaging controller 20 is received, the second CPU 31 causes the printer 40 to print these dates, as well as words such as "Sell by" and the name of the production plant, on the basis of the print data.

5                   As shown in Fig. 3C, the correlation data memory 25 stores the packaging condition numbers and the print data numbers in a correlated manner. The first CPU 21 serves to output to the printer controller 30 the printing condition numbers corresponding to inputted packaging condition numbers.

10                   Next, the operation of the packaging system of this invention will be explained. First, the registration process will be described.

                  When the system is started up, a display as shown in Fig. 5A appears on the touch screen 26, including display columns such as "No." for packaging condition number, "Name" for packaging condition name, "Bag Width", "Bag Length", "Speed," and "Print Data" as well as buttons such as "Set" 15 for a set button 26a and "Start" for a start button 26h. When the operator touches the set button 26a, a display as shown in Fig. 5B appears for setting packaging conditions. This display includes not only an input box 26c for the packaging condition number ("Preset No.") and a name selection button ("Name (A-Z)") 26d but also buttons for setting a bag length, a speed and a bag width, as 20 well as a print data selecting button 26b ("Date"). The operator touches the name-input box 26e to display an input screen (not shown) with letter and number buttons and, after a packaging condition number and a packaging condition name are inputted, packaging conditions are inputted by touching input buttons 26f on the screen. The first CPU 21 then stores the inputted values in the 25 packaging condition memory 24. The packaging conditions stored in the packaging condition memory 24 can be displayed as a list by touching the name selection button 26d and selections can also be made from this displayed list.

                  If the operator touches the print data selection button 26b thereafter, the second CPU 31 retrieves the print data number and print data 30 name from the print data memory 34 and outputs them to the packaging

controller 20, while the first CPU 21 displays a screen as shown in Fig. 5C for selecting print data, including not only the print data number and the print data name but also scroll buttons 26i and a setting ("OK") button 26j. The operator touches the scroll buttons 26i to scroll the screen and touches the print data No. or the print data name of the print data corresponding to the packaging condition set, as explained above, on the screen for selecting packaging conditions. If the operator touches the setting button 26j thereafter, the first CPU 21 functions to correlate this print data number with the packaging condition number and stores this correspondence in the correlation data memory 25. Thereafter, the packaging condition name and the packaging condition number which have been set are displayed in their respective display boxes ("No." and "Name") 60, and the corresponding print data number and print data name are displayed in the corresponding box 61, as shown in Fig. 5D.

In summary, packaging conditions for the packaging machine 200 and print data for the printer 40 can be set in proper correlation and inputted from the single packaging controller 20.

For retrieving print data stored in the correlation data memory 25, the operator selects a packaging condition number on a display (not shown) for retrieving packaging conditions, causing the first CPU 21 to search the correlation data memory 25 on the basis of the packaging condition number and to retrieve and output to the printer controller 30 the corresponding print data number. On the basis of this print data number received from the first CPU 21, the second CPU 31 sets to the printer 40 the print data from the print data memory 34 corresponding to this print data number. At the same time, the first CPU 21 causes to display on the touch screen 26 not only the specified packaging condition number and the packaging condition but also the print data number and the print data name, as shown in Fig. 5D.

When the production of the packaged products M1 is started thereafter by setting up the other components 51 of the system by controlling what was referred to above as "another controller 50", the packaging machine

200 carries out package making operations on the basis of the packaging conditions set by the packaging controller 20 and the printer 40 begins to print on the basis of the print data corresponding to these packaging conditions.

In summary, the correspondence between the packaging  
 5 conditions for the packaging machine 200 and the print data for the printer 40 is stored in the correlation data memory 25. If correlation data from the correlation data memory 25 are retrieved once, it becomes unnecessary from the next time to set the printer controller 30. Another advantage is that the operator can be protected against the danger of making errors in setting data because the  
 10 correlation data are stored in the correlation data memory 25.

The example described above is not intended to limit the scope of the invention. Many modifications and variations are possible within the scope of the invention. Fig. 6 shows another embodiment of the invention characterized wherein use is made of a single packaging-printing controller 20A which  
 15 possesses the functions of both the packaging controller 20 and the printer controller 30. As shown in Fig. 6, the packaging-printing controller 20A also comprises a CPU 21A, a ROM 22A, a RAM 23A and a clocking device 35, the RAM 23A including a packaging condition memory 24, a correlation data memory 25 and a print data memory 34. A packaging machine 200, a touch  
 20 screen 26, an optical detector 27, a printer 40 and another controller 50 as described above are each connected to this packaging-printing controller 20A through a respective interface (not shown). In other words, the packaging conditions of the packaging controller 20 and the print data of the printer controller 30 may be correlated by means of the single packaging-printing  
 25 controller 20A. The touch screen 26 may be used for inputting print data such that the personal computer 8 of Fig. 6 can be dispensed with. Moreover, the setting of the other components 51 of the system, such as the combinational weigher 1, may be carried out by using the same packaging-printing controller 20A, instead of the controller 50 connected to these other components 51.

The disclosure is intended to be interpreted broadly. For example, although the printer 40 was described above as a device for directly making prints on the film F, a combination of a label printer for making prints on a label and a label applicator for attaching a printed label on the film F is intended to be also  
5 included what is herein referred to as the "printer".

In summary, the present invention makes it possible to set and input packaging conditions for a packaging machine and print data for a printer in a correctly correlated manner for a packaging system incorporating both the packaging machine and the printer. By storing data on this correlation in a  
10 memory, the operator is no longer required to set many mutually correlated data at the beginning of each operation. This reduces the probability of an input error in correlating packaging and printer data.

What is claimed is:

1. A packaging system comprising:
  - a packaging machine which transports a bag-making film along a path
  - 5 while forming said film into a tubular form, fills said tubularly formed film with articles to be packaged and seals said film to produce a packaged product;
  - a printer disposed along said path for printing specified print data and causing said printed specified print data to appear on said film;
  - a packaging condition memory which stores packaging conditions for
  - 10 operating said packaging machine;
  - a print data memory which stores print data from which said specified print data are specified; and
  - a correlation data memory which stores correlation data between said print data and said packaging conditions.
2. The packaging system of claim 1 wherein said correlation data memory stores specified ones of said print data in correlation with specified ones of said packaging conditions.
3. The packaging system of claim 1 further comprising an input device for allowing a user to input specified ones of said packaging conditions.
4. The packaging system of claim 3 wherein said correlation data memory stores corresponding ones of said print data in correlation with those of said packaging conditions specified through said input device.
5. The packaging system of claim 1 further comprising a display device for displaying said print data in correlation with said packaging conditions.

6. The packaging system of claim 2 further comprising a display device for displaying said specified ones of said print data in correlation with specified ones of said packaging conditions.

7. The packaging system of claim 3 further comprising a display device for displaying corresponding ones of said print data in correlation with said specified ones of said packaging conditions.

8. The packaging system of claim 4 further comprising a display device for displaying said corresponding ones of said print data in correlation with said specified ones of said packaging conditions.

9. The packaging system of claim 1 wherein said packaging condition memory, said print data memory and said correlation data memory are parts of a controller means for operating said packaging machine according to a selected one of said packaging conditions and said printer by data in said print data  
5 memory correlated to said selected packaging condition according to said correlation data in said correlation data memory.

10. The packaging system of claim 2 wherein said packaging condition memory, said print data memory and said correlation data memory are parts of a controller means for operating said packaging machine according to a selected one of said packaging conditions and said printer by data in said print data  
5 memory correlated to said selected packaging condition according to said correlation data in said correlation data memory.

11. The packaging system of claim 3 wherein said packaging condition memory, said print data memory and said correlation data memory are parts of a controller means for operating said packaging machine according to a selected one of said packaging conditions and said printer by data in said print data

- 5 memory correlated to said selected packaging condition according to said correlation data in said correlation data memory.

12. The packaging system of claim 4 wherein said packaging condition memory, said print data memory and said correlation data memory are parts of a controller means for operating said packaging machine according to a selected one of said packaging conditions and said printer by data in said print data  
5 memory correlated to said selected packaging condition according to said correlation data in said correlation data memory.

13. The packaging system of claim 5 wherein said packaging condition memory, said print data memory and said correlation data memory are parts of a controller means for operating said packaging machine according to a selected one of said packaging conditions and said printer by data in said print data  
5 memory correlated to said selected packaging condition according to said correlation data in said correlation data memory.

14. The packaging system of claim 6 wherein said packaging condition memory, said print data memory and said correlation data memory are parts of a controller means for operating said packaging machine according to a selected one of said packaging conditions and said printer by data in said print data  
5 memory correlated to said selected packaging condition according to said correlation data in said correlation data memory.


15. The packaging system of claim 7 wherein said packaging condition memory, said print data memory and said correlation data memory are parts of a controller means for operating said packaging machine according to a selected one of said packaging conditions and said printer by data in said print data  
5 memory correlated to said selected packaging condition according to said correlation data in said correlation data memory.



5



Abstract of the Disclosure

A packaging system includes, in addition to a packaging machine  
5 of a known form-fill-seal type and a printer for printing on a bag-making film, a  
packaging condition memory which stores packaging conditions for operating the  
packaging machine, a print data memory which stores print data for operating the  
printer, and a correlation data memory which stores the correlation data between  
the packaging conditions and the print data. If a packaging condition is selected  
10 through an input device, not only is the packaging machine operated under the  
specified condition but also the printer is operated by the data which correspond  
to the selected packaging condition according to the correlation data stored in the  
correlation data memory.





PACKAGING CONDITION No.	PACKAGING CONDITION NAME	BAG LENGTH	BAG WIDTH	SPEED	SEAL TIME
3	Snack Salted 30g	130	120	90	200
4	Chips Salted 70g	300	250	45	200
5	Chips Salted 30g	130	120	90	120

Fig. 3A

PRINT DATA No.	PRINT DATA NAME	FONT	LETTER SIZE	LETTER SPACE	LINE SPACE	WIDTH POSITION	LENGTH POSITION	BAR CODE
10	Chips A	Gothic	10	4	8	357	45	No
11	Chips B	Gothic	10	4	8	357	45	No
12	Snack C	Mincho	12	3	7	300	30	Yes
13	Snack D	Mincho	12	3	7	300	30	Yes

Fig. 3B

PACKAGING CONDITION No.	PRINT DATA No.
3	12
4	10
5	11

Fig. 3C




Fig. 4A




Fig. 4B




Fig. 4C

26

No.	Name	Bag Width	Bag Length
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
Speed	Seal Time	Print Data	<input type="text" value="Preset"/>
<input type="text"/>	<input type="text"/>	<input type="text"/>	
<input type="button" value="Set"/>	<input type="button" value="Onetime"/>	<input type="button" value="Tube"/>	<input type="button" value="Start"/>

26a

Fig. 5A

26h

Preset No.	Name (A-Z)		Chips Salted 30g	
<input type="text" value="5"/>				
<input type="button" value="▲"/>	<input type="text" value="Bag Length"/>	<input type="text" value="Speed"/>	<input type="text" value="Seal Time"/>	
<input type="button" value="▼"/>	<input type="text" value="Strip Length"/>	<input type="text" value="Bag Width"/>	<input type="text" value="Pressure"/>	
	<input type="text" value="Adjust"/>	<input type="text" value="Date"/>	<input type="text" value="Exit"/>	

26c

26d

26e

26f

Fig. 5B

26b

26

No.	PRODUCT NAME
10	Chips A
11	Chips B
12	Snack C

Buttons: NO LABEL, COPY, EXIT, OK, Up Arrow (26i), Down Arrow (26i)

Fig. 5C

No.	Name	Bag Width	Bag Length
5	Chips Salted 30g	130	90

Buttons: Speed (120), Seal time (120), Print Data (11: Chips B), Preset, Set, Onetime, Tube, Start

Fig. 5D

DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

As a below-named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled PACKAGING SYSTEM INCORPORATING A PRINTER, the specification of which

(check one) ☒ is attached hereto.

☐ was filed on \_\_\_\_\_ as  
Application Serial No. \_\_\_\_\_  
and was amended on \_\_\_\_\_  
(if applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge my duty to disclose to the office all information known to me to be material to patentability of this application, in accordance with Title 37, Code of Federal Regulations, §1.56, which is defined on the attached page.

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)

Priority Claimed

10-314042      Japan      15 October 1998  
(Number)      (Country)      (Day/Month/Year Filed)

☒      ☐  
Yes      No

\_\_\_\_\_  
(Number)      (Country)      (Day/Month/Year Filed)

☐      ☐  
Yes      No

\_\_\_\_\_  
(Number)      (Country)      (Day/Month/Year Filed)

☐      ☐  
Yes      No



I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulation, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Serial No.)	Filing Date)	(Status) (patented, pending, abandoned)
-----------------------------	--------------	---

(Application Serial No.)	Filing Date)	(Status) (patented, pending, abandoned)
-----------------------------	--------------	---

(Application Serial No.)	Filing Date)	(Status) (patented, pending, abandoned)
-----------------------------	--------------	---

I hereby appoint the following attorneys to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith: Gerald P. Parsons, Reg. No. 24,486; Martin F. Majestic, Reg. No. 25,695; J. Suzanne Siebert, Reg. No. 28,758; James S. Hsue, Reg. No. 29,545; Alison de Runtz, Reg. No. 37,119; Keiichi Nishimura, Reg. No. 29,093;

\_\_\_\_\_; provided that if any one of said attorneys ceases being affiliated with the law firm of Majestic, Parsons, Siebert & Hsue, P.C. as partner, employee or of counsel, such attorney's appointment as attorney and all powers derived therefrom shall terminate on the date such attorney ceases being so affiliated.

Direct all telephone calls to KEIICHI NISHIMURA at (415) 248-5500.

Address all correspondence to:



Customer No.: 020227

**020227**

PATENT TRADEMARK OFFICE

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Title 18, United

States Code, §1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or  
first inventor:

Akira Ishino

Inventor's signature:

Akira Ishino

Date:

29 September 1999

Residence:

Shiga, Japan

Citizenship:

Japan

Post Office Address:

c/o ISHIDA CO., LTD.

Shiga Integrated Facility

959-1 Shimomagari, Ritto-cho, Kurita-gun

Shiga 520-3026, Japan

Full name of second joint  
inventor, if any:

Katsuaki Kouno

Inventor's signature:

Katsuaki Kouno

Date:

29 SEPTEMBER 1999

Residence:

Shiga, Japan

Citizenship:

Japan

Post Office Address:

c/o ISHIDA CO., LTD.

Shiga Integrated Facility

959-1 Shimomagari, Ritto-cho, Kurita-gun

Shiga 520-3026, Japan

Full name of third joint  
inventor, if any:

Colin Buckley

Inventor's signature:

Colin Buckley

Date:

1st October 1999

Residence:

Birmingham, Great Britain

Citizenship:

Great Britain

Post Office Address:

c/o ISHIDA Europe Manufacturing Limited

11 Kettles Wood Drive, Woodgate Business

Park, Birmingham, B32 3DB, Great Britain

### Section 1.56 Duty to Disclose Information Material to Patentability.

(a) A patent by its very nature is affected with a public interest. The public interest is best served, and the most effective patent examination occurs when, at the time an application is being examined, the Office is aware of and evaluates the teachings of all information material to patentability. Each individual associated with the filing and prosecution of a patent application has a duty of candor and good faith in dealing with the Office, which includes a duty to disclose to the Office all information known to that individual to be material to patentability as defined in this section. The duty to disclose information exists with respect to each pending claim until the claim is cancelled or withdrawn from consideration, or the application becomes abandoned. Information material to the patentability of a claim that is cancelled or withdrawn from consideration need not be submitted if the information is not material to the patentability of any claim remaining under consideration in the application. There is no duty to submit information which is not material to the patentability of any existing claim. The duty to disclose all information known to be material to patentability is deemed to be satisfied if all information known to be material to patentability of any claim issued in a patent was cited by the Office or submitted to the Office in the manner prescribed by §§ 1.97(b)-(d) and 1.98. However, no patent will be granted on an application in connection with which fraud on the Office was practiced or attempted or the duty of disclosure was violated through bad faith or intentional misconduct. The Office encourages applicants to carefully examine:

- (1) prior art cited in search reports of a foreign patent office in a counterpart application, and
- (2) the closest information over which individuals associated with the filing or prosecution of a patent application believe any pending claim patentably defines, to make sure that any material information contained therein is disclosed to the Office.

(b) Under this section, information is material to patentability when it is not cumulative to information already of record or being made of record in the application, and

- (1) It establishes, by itself or in combination with other information, a prima facie case of unpatentability of a claim; or
- (2) It refutes, or is inconsistent with, a position the applicant takes in:
  - (i) Opposing an argument of unpatentability relied on by the Office, or
  - (ii) Asserting an argument of patentability.

A prima facie case of unpatentability is established when the information compels a conclusion that a claim is unpatentable under the preponderance of evidence, burden-of-proof standard, giving each term in the claim its broadest reasonable construction consistent with the specification, and before any consideration is given to evidence which may be submitted in an attempt to establish a contrary conclusion of patentability.

(c) Individuals associated with the filing or prosecution of a patent application within the meaning of this section are:

- (1) Each inventor named in the application;
- (2) Each attorney or agent who prepares or prosecutes the application; and
- (3) Every other person who is substantively involved in the preparation or prosecution of the application and who is associated with the inventor, with the assignee or with anyone to whom there is an obligation to assign the application.

(d) Individuals other than the attorney, agent or inventor may comply with this section by disclosing information to the attorney, agent, or inventor.